

SOCKET SET SCREWS CUP POINT

J *H* *J*

Nominal Size or Basic Screw Diameter	Hexagon Socket Size	Min. Key Engagement to Develop Functional Capability of Key	Cup Point Diameters
--------------------------------------	---------------------	---	---------------------

		Nom	Hex Socket T_H Min	Max	Min
0	0.0600	0.028	0.050	0.033	0.027
1	0.0730	0.028	0.060	0.040	0.033
2	0.0860	0.035	0.060	0.047	0.039
3	0.0990	0.050	0.070	0.054	0.045
4	0.1120	0.050	0.070	0.061	0.051
5	0.1250	1/16	0.062	0.067	0.057
6	0.1380	1/16	0.062	0.074	0.064
8	0.1640	5/64	0.078	0.087	0.076
10	0.1900	3/32	0.094	0.102	0.088
1/4	0.2500	1/8	0.125	0.132	0.118
5/16	0.3125	5/32	0.156	0.172	0.156
3/8	0.3750	3/16	0.188	0.212	0.194
7/16	0.4375	7/32	0.219	0.252	0.232
1/2	0.5000	1/4	0.250	0.291	0.270
5/8	0.6250	5/16	0.312	0.371	0.347
3/4	0.7500	3/8	0.375	0.450	0.425
7/8	0.8750	1/2	0.500	0.530	0.502
1	1.0000	9/16	0.562	0.609	0.579
1 1/8	1.1250	9/16	0.562	0.689	0.655
1 1/4	1.2500	5/8	0.625	0.767	0.733
1 3/8	1.3750	5/8	0.625	0.848	0.808
1 1/2	1.5000	3/4	0.750	0.926	0.886
1 3/4	1.7500	1	1.000	1.086	1.039
2	2.0000	1	1.000	1.244	1.193